

OXESS Specifications (2013-2014)

Model	Type	Glass	Carbon	Titanal	Titanal/ Carbon	Zebrano	Length	Edge	Radius	min. Width	Stance
RS 137	Kids	x	x			x	1.37 m	1.24 m	8.0 m	178 mm	410 mm
RS 145	Kids	x	x			x	1.45 m	1.31 m	10.0 m	192 mm	460 mm
RS 154	SL		x	x		x	1.54 m	1.39 m	9.0 m	184 mm	480 mm
RS 160	SL		x	x		x	1.60 m	1.45 m	9.5 m	195 mm	500 mm
RS 162	SL		x	x		x	1.62 m	1.47 m	10.0 m	198 mm	500 mm
RS 164	SL		x	x		x	1.64 m	1.50 m	11.5 m	197 mm	500 mm
RG 170	GS		x	x		x	1.70 m	1.56 m	14.0 m	186 mm	480 mm
RG 174	GS		x	x		x	1.74 m	1.60 m	14.5 m	188 mm	480 mm
RG 178	GS		x	x		x	1.78 m	1.64 m	15.0 m	198 mm	500 mm
RG 180	GS		x	x		x	1.80 m	1.66 m	17.0 m	196 mm	480 mm
RG 185 17.0	GS		x	x		x	1.85 m	1.71 m	17.0 m	197 mm	500 mm
RG 185 19.0	GS		x	x		x	1.85 m	1.71 m	19.0 m	201 mm	500 mm
XR168	Carving		x				1.68 m	1.54 m	10.0 m	178 mm	500 mm
XR178	Carving		x				1.78 m	1.64 m	11.5 m	182 mm	520 mm
XR 193	Carving		x				1.93 m	1.79 m	17.0 m	187 mm	540 mm
eXR174	Carving		x				1.74 m	1.60 m	13.0/19.0 m	219 mm	510 mm
SX174	Skwal		x				1.74 m	1.60 m	10.5 m	111 mm	400 mm
SX178	Skwal		x				1.78 m	1.64 m	14.0 m	119 mm	400 mm
XX168	Hardcarve		x		x	x	1.68 m	1.54 m	9.5 m	152 mm	480 mm
XX178	Hardcarve		x		x	x	1.78 m	1.64 m	11.0 m	155 mm	520 mm
XX185	Hardcarve		x		x	x	1.85 m	1.71 m	13.0 m	156 mm	520 mm
XX193	Hardcarve		x		x	x	1.93 m	1.79 m	13.5 m	150 mm	540 mm
FX 157	Freeride	x	x		x		1.57 m	1.32 m	9.5 m	245 mm	520 mm
FX 163	Freeride	x	x		x		1.63 m	1.39 m	10.0 m	254 mm	540 mm
FX 168	Freeride	x	x		x		1.68 m	1.43 m	10.0 m	252 mm	550 mm
BX145	SBX	x	x		x		1.45 m	1.24 m	10.0 m	248 mm	520 mm
BX151 9.5	SBX	x	x		x		1.51 m	1.32 m	9.5 m	245 mm	520 mm
BX151 11.0	SBX	x	x		x		1.51 m	1.32 m	11.0 m	241 mm	520 mm
BX155 11.0	SBX	x	x		x		1.55 m	1.36 m	11.0 m	245 mm	540 mm
BX155 13.0	SBX	x	x		x		1.55 m	1.36 m	13.0 m	246 mm	540 mm
BX159 10.0	SBX	x	x		x		1.59 m	1.39 m	10.0 m	254 mm	540 mm
BX159 12.0	SBX	x	x		x		1.59 m	1.39 m	12.0 m	258 mm	540 mm
BX163 10.0	SBX	x	x		x		1.63 m	1.43 m	10.0 m	252 mm	550 mm
BX163 12.0	SBX	x	x		x		1.63 m	1.43 m	12.0 m	261 mm	550 mm
BX163 14.5	SBX	x	x		x		1.63 m	1.43 m	14.5 m	258 mm	550 mm
BX163 16.0	SBX	x	x		x		1.63 m	1.43 m	16.0 m	260 mm	560 mm
X-1	SBX	x	x		x		1.69 m	1.49 m	17.0 m	260 mm	550 mm